



BUNTON TUBE

Please note: We specialize in non - standard items.

If you require any size, length or grade not on this list, please do not hesitate to contact our sales team.

THEORETICAL BUNTON CHARACTERISTICS				ACTUAL DRAWN BUNTON CHARACTERISTICS				LENGTHS AVAILABLE (M)	MANUFACTURING STANDARD	MATERIAL GRADE
DIMENSIONS (MM)	WALL THICKNESS (MM)	KILOGRAMS PER METER	REQUIRED INPUT TUBE Ø	DIMENSIONS (MM)	WALL THICKNESS (MM)	KILOGRAMS PER METER	AVAILABLE INPUT TUBE Ø			
203.2 x 101.6	8.0	31.27	166.28	205.66 x 102.83	7.11	28.26	168.3	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	38.54	166.28		10.97	42.56	168.3	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
203.2 x 152.4	8.0	34.86	184.74	209 x 156.75	8.0	35.90	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	43.09	184.74		10.0	44.39	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
228.6 x 101.6	8.0	34.41	182.45	238.05 x 105.8	8.0	35.90	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	42.52	182.45		10.0	44.39	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
228.6 X 152.4	8.0	38.05	200.91	216.18 X 144.12	8.0	35.90	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	47.07	200.91		10.0	44.39	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
254 x 101.6	8.0	37.60	198.62	242.98 x 97.19	8.0	35.90	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	46.51	198.62		10.0	44.39	190	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
254 x 152.4	8.0	41.24	217.08	256.37 x 153.82	8.0	41.63	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	51.06	217.08		10.0	51.55	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
279.4 x 101.6	8.0	40.79	214.79	285.01 x 103.64	8.0	41.63	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	50.50	214.79		10.0	51.55	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
300 x 150	8.0	46.85	245.50	298.8 x 149.4	8.0	46.65	244.5	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	58.07	245.49		10.0	57.83	244.5	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
304.8 x 101.6	8.0	43.98	230.96	289.15 x 96.38	8.0	41.63	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	54.48	230.96		10.0	51.55	219	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
342.9 x 152.4	8.0	52.41	273.67	342.05 x 152.02	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	65.02	273.67		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
355.6 x 101.6	8.0	50.36	263.30	368.7 x 105.34	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	62.46	263.30		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
355.6 x 127	8.0	52.18	272.53	356.22 x 127.22	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	64.74	272.53		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
355.6 x 152.4	8.0	54.00	281.76	344.55 x 147.67	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	67.01	281.76		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
381 x 101.6	8.0	53.55	279.47	372.19 x 99.25	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	66.45	279.47		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
381 x 127	8.0	55.37	288.70	360.29 x 120.09	8.0	52.29	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	68.72	288.70		10.0	64.87	273	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
406.4 x 152.4	8.0	60.38	314.10	418.95 x 157.11	8.0	62.35	323.9	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	74.99	314.10		10.0	77.45	323.9	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
457.2 x 152.4	8.0	66.76	346.44	469.29 x 156.43	8.0	68.67	355.6	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	82.96	346.44		10.0	85.34	355.6	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
482.6 x 127	8.0	68.13	353.38	485.63 x 127.8	8.0	68.67	355.6	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355
	10.0	84.67	353.38		10.0	85.34	355.6	6.1 / 9.144 / 12.2	SANS 657-1(Def 3.1)	S 235 or S 355