



SPIRAL WELDED PIPE(LARGE BORE)

Please note: We specialize in non - standard items.

If you require any size, length or grade not on this list, please do not hesitate to contact our sales team.

SIZE	WALL	AVAILABLE (M)	KILOGRAMS PER METER	MANUFACTURING STANDARD	MATERIAL GRADE	SANS 719		
						GRADE B	GRADE C	GRADE D
(MM)	(MM)					strength 241	strength 290	strength 355
						TEST PRESSURE RATING KPa		
711	6.0	6.1 / 9.144 / 12.2	104.330	SANS 719 / API 5L SPIRAL	GR C / X42	3050	3670	4490
	8.0	6.1 / 9.144 / 12.2	138.720	SANS 719 / API 5L SPIRAL	GR C / X42	4070	4890	5990
	10.0	6.1 / 9.144 / 12.2	172.900	SANS 719 / API 5L SPIRAL	GR C / X42	5080	6110	7480
762	6.0	6.1 / 9.144 / 12.2	111.880	SANS 719 / API 5L SPIRAL	GR C / X42	2840	3420	4190
	8.0	6.1 / 9.144 / 12.2	148.780	SANS 719 / API 5L SPIRAL	GR C / X42	3790	4560	5590
	10.0	6.1 / 9.144 / 12.2	185.480	SANS 719 / API 5L SPIRAL	GR C / X42	4740	5700	6980
813	6.0	6.1 / 9.144 / 12.2	119.430	SANS 719 / API 5L SPIRAL	GR C / X42	2670	3210	3930
	8.0	6.1 / 9.144 / 12.2	158.840	SANS 719 / API 5L SPIRAL	GR C / X42	3560	4280	5240
	10.0	6.1 / 9.144 / 12.2	198.060	SANS 719 / API 5L SPIRAL	GR C / X42	4450	5350	6550
914	6.0	6.1 / 9.144 / 12.2	134.370	SANS 719 / API 5L SPIRAL	GR C / X42	2370	2850	3490
	8.0	6.1 / 9.144 / 12.2	178.770	SANS 719 / API 5L SPIRAL	GR C / X42	3160	3800	4660
	10.0	6.1 / 9.144 / 12.2	222.970	SANS 719 / API 5L SPIRAL	GR C / X42	3960	4750	5820
1016	6.0	6.1 / 9.144 / 12.2	149.470	SANS 719 / API 5L SPIRAL	GR C / X42	2130	2560	3140
	8.0	6.1 / 9.144 / 12.2	198.900	SANS 719 / API 5L SPIRAL	GR C / X42	2840	3420	4190
	10.0	6.1 / 9.144 / 12.2	248.130	SANS 719 / API 5L SPIRAL	GR C / X42	3550	4280	5240